



## PRINTER 250

The standard for performance, reliability and adaptability. With millions shipped worldwide, the PRINTER 250 meets the needs of more merchants than any other point-of-sale printer.

There's one sure way to increase your productivity—add the world's most popular POS printer to your VeriFone® system.

The value leader among compact point-of-sale printers, the PRINTER 250 maximizes the capabilities of your VeriFone system. It generates crisply printed two- or three-part receipts just seconds after you enter a transaction through the VeriFone system. This gives you a very short total transaction time—the true test of a POS system's efficiency. And the PRINTER 250 provides a complete audit trail that you can compare with the electronic record for accurate balancing at the close of the business day.

### **More Efficient Operation, Lower Cost Of Ownership**

Designed expressly for use with your VeriFone system, the PRINTER 250 offers you more performance and greater reliability for your money.

With its integrated paper-path feed, the PRINTER 250 virtually eliminates paper jamming. It also warns you when your paper is low, so you'll never run out in the middle of a transaction.

Convenient drop-in ribbon cartridges mean cleaner, easier ribbon replacement. And the PRINTER 250 can save you the expense of ribbons altogether—operating in the impact mode with specially treated paper.

You can ensure that your PRINTER 250 will continue to perform at maximum efficiency by ordering top-quality paper, ribbon and other supplies directly from VeriFone at very competitive prices.

### **A Versatile Complement To Your VeriFone System**

The PRINTER 250 works with all VeriFone transaction systems and with many non-VeriFone terminals. And the PRINTER 250 is a proven performer in a multitude of environments—including grocery stores, department stores, pharmacies, gas stations and convenience stores. It is also a cost-effective printing solution for lottery as well as time and attendance applications.

The PRINTER 250 support 11 international character sets and graphics. It is available in the same color options as VeriFone transaction systems, giving you a fully integrated presentation at the point of sale.

# PRINTER 250

## Features

- Compatible with all VeriFone transaction systems
- Can interface with non-VeriFone terminals
- Saves valuable counterspace with its compact design
- Uses easy-to-change drop-in ribbon cartridges
- Can operate in a ribbonless mode with specially treated paper
- Comes with an integrated paper path feed that virtually eliminates paper jams
- Includes power-on/paper-low indicators
- Produces crisp, legible characters with fast, reliable dot matrix shuttle printing

## Specifications

### Physical

|                       |                             |
|-----------------------|-----------------------------|
| Height                | 4.1 in (105 mm)             |
| Width                 | 6.1 in (155 mm)             |
| Depth                 | 8.9 in (225 mm)             |
| Shipping Weight       | 7 lbs (3.2 kg)              |
| Operating Temperature | 0° to 40° C (32° to 104° F) |

### Printing

|                            |  |
|----------------------------|--|
| Method                     | 7-pin shuttle-impact dot matrix  |
| Speed                      | 2.1 lines per second (may vary depending on the terminal application)  |
| Buffer                     | 3 line   |
| Print Head Life Expectancy | 50 million characters  |
| Mechanism Reliability      | 1.5 million lines MCBF (Mean Cycles Between Failures)  |
| Characters                 | 11 sets: US, UK, French, German, Danish I, Danish II, Swedish, Italian, Spanish, Norwegian, Arabic<br>Graphics printing capability |

### Ribbon

|       |   |
|-------|---|
| Type  | Cartridge                               |
| Color | Dual Color (red/black) and single color |

### Paper

|        |                                   |
|--------|-----------------------------------|
| Size   | 3.0 in (76 mm) wide standard roll |
| Format | 42-column, portrait               |

### Interface

|           |   |
|-----------|---|
| Serial    | RS-232C compatible                                |
| Baud Rate | Switch selectable; 1200, 2400, 4800 and 9600 baud |

### Power

|         |  |
|---------|--|
| Voltage | 120 VAC, 47–63 Hz (±10%) or 220 VAC, 50 Hz |
|---------|--|

